



EZ17E TECHNICAL SPECIFICATIONS

Operating data

Shipping weight min.	1,681 kg
Operating weight	1,797 - 2,152 kg
Operating weight min.	1,797 kg
Biting force max.	9.1 kN
Breakout force max.	20.5 kN
Digging depth max.	2,490 mm
Digging radius max.	4,060 mm
L x W x H	3,584 x 990 x 2,660 mm

Engine / Motor Electric engine

Rated voltage	48 V
Rated performance	16.5 kW
Capacity	23.4 kWh
RPM / speed	2,200 rpm

Battery Rated voltage

Current Continuous current	48 V
Current Maximum current, short-term	220 A
Hydraulic system	350 A

Duty pump

Flow rate	Variable displacement pump
Operating pressure for working and traction hydraulics	39.6 l/min
Undercarriage	240 bar

Travel speed max.

4.5Km/h

Sound level

(LwA) according to 2000/14/EC	84 dB(A)
Cabin - specified sound pressure level LpA according to ISO 6394	70 dB(A)

Due to its zero emissions, the EX17E is ideal for indoor applications, as well as in areas where exhaust fumes and noise are restricted. Thanks to the powerful lithium ion battery, it can be used for a typical workday and, if necessary, continue to be used in stationary operation connected to a power source. Due to its patented battery technology with integrated battery heating, the unit can be charged at any power source (100 to 415 V).